



COBRA CUSTOM CAPABILITIES

DRIVERS		STOCK LOFT	CUSTOM LOFT	STOCK LIE	CUSTOM LIE	STOCK LENGTH	CUSTOM LENGTH
ZL Encore		8.5; 9.5; 10.5; 11.5"	N/A	*59°	N/A	45.25; 45.5; 45.75; 46"	Max/Min Length ±1"
Amp		8.5; 9.5; 10.5; 11.5"	N/A	*59°	N/A	45.25; 45.5; 45.75; 46"	Max/Min Length ±1"
Amp Offset		10.5; 11.5"	N/A	*59°	N/A	45.75; 46"	Max/Min Length ±1"
Amp Women's		13°	N/A	*58°	N/A	44.25"	Max/Min Length ±1"
Amp Offset Women's		15°	NA	*58°	NA	44.25"	Max/Min Length ±1"
FAIRWAYS	MODEL	STOCK LOFT	CUSTOM LOFT	STOCK LIE	CUSTOM LIE	STOCK LENGTH	CUSTOM LENGTH
Baffler T-Rail	3+, 3, 5, 7	13; 16; 18; 20"	N/A	57; 57; 58; 59°	N/A	43; 43; 42.5; 42"	Max/Min Length ±1"
Baffler T-Rail Women's	3, 5, 7	18; 20; 22"	N/A	58; 59; 60°	N/A	42; 41.5; 41"	Max/Min Length ±1"
Amp	3, 4, 5	15; 16.5; 18"	N/A	57; 57.5; 58°	N/A	43.5; 43.25; 43"	Max/Min Length ±1"
Long Tom 2-wood**		12.5°	NA	57°	NA	45.19"	Max/Min Length ±1"
HYBRIDS	MODEL	STOCK LOFT	CUSTOM LOFT	STOCK LIE	CUSTOM LIE	STOCK LENGTH	CUSTOM LENGTH
Amp	2H, 3H, 4H	17; 19; 22°	N/A	58; 58.5; 59°	N/A	40.75; 40.25; 39.75"	Max/Min Length ±1"
Baffler T-Rail	2H, 3H, 4H, 5H, 6H, 7H	17; 19; 22; 25; 28; 31°	N/A	58.5; 59; 59.5; 60; 60.5; 61°	N/A	41; 40.5; 40; 39.5; 39"	Max/Min Length ±1"
Baffler T-Rail Women's	3H, 4H, 5H, 6H, 7H	22; 25; 28; 31; 34°	N/A	59.5; 60; 60.5; 61; 61.5°	N/A	39.5; 39; 38.5; 38; 37.5"	Max/Min Length ±1"
IRONS	MODEL	STOCK LOFT	CUSTOM LOFT	STOCK LIE	CUSTOM LIE	STOCK LENGTH	CUSTOM LENGTH
Amp	7-iron	31°	Loft ±1°	62.5°	Lie +4°/-2°	37.25"	Max/Min Length +1.5°/-1.0°
Amp Women's	6-iron, PW	28; 44°	Loft ±1°	61; 63°	Lie +4°/-2°	36.5; 34.75"	Max/Min Length +1.5°/-1.0°
Amp Forged	7-iron	33°	Loft ±1°	62.5°	Lie +4°/-2°	37.25"	Max/Min Length +1.5°/-1.0°
S3 Max	7-iron	31°	Loft ±1°	62.5°	Lie ±4°	37.25"	Max/Min Length +1.5°/-1.0°
WEDGES		STOCK LOFT	CUSTOM LOFT	STOCK LIE	CUSTOM LIE	STOCK LENGTH	CUSTOM LENGTH
Trusty Rusty		49; 51; 53; 55; 57; 59; 61°	Loft ±1°	64°	Lie ±2°	35.5; 35.5; 35.5; 35.25; 35.25; 35; 35	Max/Min Length ±1"
Big Trusty Rusty		50; 55; 60°	Loft ±1°	64°	Lie ±2°	35.5; 35.25; 35"	Max/Min Length ±1"

*Lie listed in (N) neutral setting; Varies per Adjustable Flight Technology™ setting, **Only length changes allowed

CUSTOM CAPABILITIES